

Environment Variables

Environment Variables are used to store commonly used parameters or settings in the application. Storing commonly used values in one place eases the migration and maintenance of the application developed. Environment variables can be retrieved by using the [Environment Variable Hash Variable](#).

<input type="checkbox"/>	Id	Value	Remarks
<input type="checkbox"/>	constestId	1002	
<input type="checkbox"/>	jdbcPassword		
<input type="checkbox"/>	jdbcUrl	jdbc:mysql://localhost:3306	jdbc:mysql://localhost:3306
<input type="checkbox"/>	jdbcUsername	root	
<input type="checkbox"/>	webroot	http://localhost:8080/	

Figure 1: Environment Variables

In the figure above, one can make use of the Environment Variable to store commonly used values in places like [Email Tool](#), [Database Update Tool](#), and so on. Doing so makes it easier to manage setting/configuration changes.

Plugin Configuration - Update Database

Configure Database Update Tool

Configure Database Update Tool > Query

Datasource: Custom Datasource

Custom JDBC Driver: com.mysql.jdbc.Driver

Custom JDBC URL *: #envVariable.jdbcUrl#

Custom JDBC Username: #envVariable.jdbcUsername#

Custom JDBC Password: [Masked]

Figure 2: Database Update Tool Configuration by Using Environment Variable