

JsonUtil

- Description
- Code Sample
- Fields
 - PROPERTY_ACTION
 - PROPERTY_ACTIONS
 - PROPERTY_BINDER
 - PROPERTY_CLASS_NAME
 - PROPERTY_COLUMNS
 - PROPERTY_DESC
 - PROPERTY_FILTER_TYPE
 - PROPERTY_FILTERS
 - PROPERTY_FORMAT
 - PROPERTY_HIDDEN
 - PROPERTY_HIDE_PAGE_SIZE
 - PROPERTY_ID
 - PROPERTY_LABEL
 - PROPERTY_NAME
 - PROPERTY_OPERATOR
 - PROPERTY_ORDER
 - PROPERTY_ORDER_BY
 - PROPERTY_PAGE_SIZE
 - PROPERTY_PROPERTIES
 - PROPERTY_RENDER_HTML
 - PROPERTY_ROW_ACTIONS
 - PROPERTY_SORTABLE
 - PROPERTY_STYLE
 - PROPERTY_WIDTH
- Methods
 - fromJson
 - generateDefaultList
 - generateDefaultList
 - parseActionFromJsonObject
 - parseActionsFromJsonObject
 - parseBinderFromJsonObject
 - parseColumnsFromJsonObject
 - parseElementFromJson
 - parseElementFromJsonObject
 - parseFiltersFromJsonObject
 - parseFilterTypeFromJsonObject
 - parseFormatterFromJsonObject
 - parseRowActionsFromJsonObject

Description

- org.joget.apps.datalist.service.JsonUtil
- Under wflow-core module
- Utility class containing methods to create datalist from JSON
- This Utility class should not use directly. Please use [DataListService](#) instead.

Code Sample

```

import org.joget.apps.app.dao.DatalistDefinitionDao;
import org.joget.apps.app.model.AppDefinition;
import org.joget.apps.app.model.DatalistDefinition;
import org.joget.apps.app.service.AppUtil;
import org.joget.apps.datalist.model.DataList;

AppService appService = (AppService) AppUtil.getApplicationContext().getBean("appService");
DatalistDefinitionDao datalistDefinitionDao = (DatalistDefinitionDao) AppUtil.getApplicationContext().getBean(
("datalistDefinitionDao"));

String id = "crm_account";
String appId = "crm";
Long appVersion = appService.getPublishedVersion(appId);

AppDefinition appDef = appService.getAppDefinition(appId, appVersion.toString());
DatalistDefinition datalistDefinition = datalistDefinitionDao.loadById(id, appDef);

DataList dataList = JsonUtil.fromJson(datalistDefinition.getJson(), DataList.class);

```

Fields

PROPERTY_ACTION

```
public static final java.lang.String PROPERTY_ACTION = "action";
```

Key to retrieve the action value from JSON Object properties

PROPERTY_ACTIONS

```
public static final java.lang.String PROPERTY_ACTIONS = "actions";
```

Key to retrieve the actions from JSON Object properties

PROPERTY_BINDER

```
public static final java.lang.String PROPERTY_BINDER = "binder";
```

Key to retrieve the binder from JSON Object properties

PROPERTY_CLASS_NAME

```
public static final java.lang.String PROPERTY_CLASS_NAME = "className";
```

Key to retrieve the class name value from JSON Object properties

PROPERTY_COLUMNS

```
public static final java.lang.String PROPERTY_COLUMNS = "columns";
```

Key to retrieve the columns from JSON Object properties

PROPERTY_DESC

```
public static final java.lang.String PROPERTY_DESC = "description";
```

Key to retrieve the description value from JSON Object properties

PROPERTY_FILTER_TYPE

```
public static final java.lang.String PROPERTY_FILTER_TYPE = "type";
```

Key to retrieve the type value from JSON Object properties

PROPERTY_FILTERS

```
public static final java.lang.String PROPERTY_FILTERS = "filters";
```

Key to retrieve the filter value from JSON Object properties

PROPERTY_FORMAT

```
public static final java.lang.String PROPERTY_FORMAT = "format";
```

Key to retrieve the format value from JSON Object properties

PROPERTY_HIDDEN

```
public static final java.lang.String PROPERTY_HIDDEN = "hidden";
```

Key to retrieve the hidden value from JSON Object properties

PROPERTY_HIDE_PAGE_SIZE

```
public static final java.lang.String PROPERTY_HIDE_PAGE_SIZE = "hidePageSize";
```

Key to retrieve the Id value from JSON Object properties

PROPERTY_ID

```
public static final java.lang.String PROPERTY_ID = "id";
```

Key to retrieve the Id value from JSON Object properties

PROPERTY_LABEL

```
public static final java.lang.String PROPERTY_LABEL = "label";
```

Key to retrieve the label value from JSON Object properties

PROPERTY_NAME

```
public static final java.lang.String PROPERTY_NAME = "name";
```

Key to retrieve the name value from JSON Object properties

PROPERTY_OPERATOR

```
public static final java.lang.String PROPERTY_OPERATOR = "operator";
```

Key to retrieve the operator value from JSON Object properties

PROPERTY_ORDER

```
public static final java.lang.String PROPERTY_ORDER = "order";
```

Key to retrieve the order value from JSON Object properties

PROPERTY_ORDER_BY

```
public static final java.lang.String PROPERTY_ORDER_BY = "orderBy";
```

Key to retrieve the order by value from JSON Object properties

PROPERTY_PAGE_SIZE

```
public static final java.lang.String PROPERTY_PAGE_SIZE = "pageSize";
```

Key to retrieve the page size value from JSON Object properties

PROPERTY_PROPERTIES

```
public static final java.lang.String PROPERTY_PROPERTIES = "properties";
```

Key to retrieve the properties values from JSON Object properties

PROPERTY_RENDER_HTML

```
public static final java.lang.String PROPERTY_RENDER_HTML = "renderHtml";
```

Key to retrieve the render html value from JSON Object properties

PROPERTY_ROW_ACTIONS

```
public static final java.lang.String PROPERTY_ROW_ACTIONS = "rowActions";
```

Key to retrieve the row actions from JSON Object properties

PROPERTY_SORTABLE

```
public static final java.lang.String PROPERTY_SORTABLE = "sortable";
```

Key to retrieve the sortable value from JSON Object properties

PROPERTY_STYLE

```
public static final java.lang.String PROPERTY_STYLE = "style";
```

Key to retrieve the style value from JSON Object properties

PROPERTY_WIDTH

```
public static final java.lang.String PROPERTY_WIDTH = "width";
```

Key to retrieve the width value from JSON Object properties

Methods

fromJson

```
public static <T extends java.lang.Object> T fromJson(java.lang.String json, java.lang.Class<T> classOfT)
```

Converts from JSON string into an object. Specifically to support data list model classes.

generateDefaultList

```
public static java.lang.String generateDefaultList(java.lang.String listId, org.joget.apps.app.model.DatalistDefinition datalistDef)
```

Used to generate a datalist definition JSON

generateDefaultList

```
public static java.lang.String generateDefaultList(java.lang.String listId, org.joget.apps.app.model.DatalistDefinition datalistDef, org.joget.apps.app.model.DatalistDefinition copyDatalistDef)
```

Used to generate a datalist definition JSON based on another datalist definition

parseActionFromJsonObject

```
public static org.joget.apps.datalist.model.DataListAction parseActionFromJsonObject(org.json.JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.IllegalAccessException
```

Used to retrieves datalist action from JSON Object

parseActionsFromJsonObject

```
public static java.util.Collection<org.joget.apps.datalist.model.DataListAction> parseActionsFromJsonObject(org.json.JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.IllegalAccessException
```

Used to retrieves datalist actions from JSON Object

parseBinderFromJsonObject

```
public static org.joget.apps.datalist.model.DataListBinder parseBinderFromJsonObject(org.json.JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.IllegalAccessException
```

Used to retrieves datalist binder from JSON Object

parseColumnsFromJsonObject

```
public static java.util.Collection<org.joget.apps.datalist.model.DataListColumn> parseColumnsFromJsonObject(org.json.JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.IllegalAccessException
```

Used to retrieves datalist column from JSON Object

parseElementFromJson

```
public static java.lang.Object parseElementFromJson(java.lang.String json)
```

Converts from JSON java.lang.String into an object. Specifically to support data list model classes.

parseElementFromJsonObject

```
public static java.lang.Object parseElementFromJsonObject(org.json.JSONObject obj) throws java.lang.Exception
```

Used to creates Datalist object from JSON Object

parseFiltersFromJsonObject

```
public static java.util.Collection<org.joget.apps.datalist.model.DataListFilter> parseFiltersFromJsonObject  
(org.json.JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.  
IllegalAccessException
```

Used to retrieves datalist filters from JSON Object

```
parseFilterTypeFromJsonObject
```

```
public static org.joget.apps.datalist.model.DataListFilterType parseFilterTypeFromJsonObject(org.json.  
JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.  
IllegalAccessException
```

Used to retrieves datalist filter type from JSON Object

```
parseFormatterFromJsonObject
```

```
public static org.joget.apps.datalist.model.DataListColumnFormat parseFormatterFromJsonObject(org.json.  
JSONObject obj) throws org.json.JSONException, java.lang.InstantiationException, java.lang.  
IllegalAccessException
```

Used to retrieves datalist formatter from JSON Object

```
parseRowActionsFromJsonObject
```

```
public static java.util.Collection<org.joget.apps.datalist.model.DataListAction>  
parseRowActionsFromJsonObject(org.json.JSONObject obj) throws org.json.JSONException, java.lang.  
InstantiationException, java.lang.IllegalAccessException
```

Used to retrieves datalist row actions from JSON Object