

Audit Trail API

Definition

Audit Trail API will list all records present in the [Audit Trail](#).

Audit Trail

List audit trails

	Name	Description
--	------	-------------

1

List audit trails

List all records present in the Audit Trail database table by default.

Able to filter or sort the returned results via parameters.

Name	Description																
URL	/auditTrails																
HTTP Method	GET																
Query String Parameters	<table border="1"><thead><tr><th>Parameter</th><th>Description</th></tr></thead><tbody><tr><td>search</td><td>Filters the response by querying the search terms for:<ul style="list-style-type: none">usernamejava classjava methodoutput messageSimilar to the LIKE operator for database querying.</td></tr><tr><td>dateFrom</td><td>Filters the response from the specified date and time. Format: YYYY-MM-DD hh:mm:ss (e.g: 2019-08-26 00:00:00)</td></tr><tr><td>dateTo</td><td>Filters the response to the specified date and time. Format: YYYY-MM-DD hh:mm:ss (e.g: 2019-08-27 23:59:59)</td></tr><tr><td>sort</td><td>Audit trails data column to sort. Must be used in conjunction with "sortDescending" parameter.</td></tr><tr><td>sortDescending</td><td>Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.</td></tr><tr><td>startOffset</td><td>Starting position of records to start query. Expects an integer.</td></tr><tr><td>pageSize</td><td>Number of results to return. Expects an integer.</td></tr></tbody></table>	Parameter	Description	search	Filters the response by querying the search terms for: <ul style="list-style-type: none">usernamejava classjava methodoutput message Similar to the LIKE operator for database querying.	dateFrom	Filters the response from the specified date and time. Format: YYYY-MM-DD hh:mm:ss (e.g: 2019-08-26 00:00:00)	dateTo	Filters the response to the specified date and time. Format: YYYY-MM-DD hh:mm:ss (e.g: 2019-08-27 23:59:59)	sort	Audit trails data column to sort. Must be used in conjunction with "sortDescending" parameter.	sortDescending	Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.	startOffset	Starting position of records to start query. Expects an integer.	pageSize	Number of results to return. Expects an integer.
Parameter	Description																
search	Filters the response by querying the search terms for: <ul style="list-style-type: none">usernamejava classjava methodoutput message Similar to the LIKE operator for database querying.																
dateFrom	Filters the response from the specified date and time. Format: YYYY-MM-DD hh:mm:ss (e.g: 2019-08-26 00:00:00)																
dateTo	Filters the response to the specified date and time. Format: YYYY-MM-DD hh:mm:ss (e.g: 2019-08-27 23:59:59)																
sort	Audit trails data column to sort. Must be used in conjunction with "sortDescending" parameter.																
sortDescending	Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.																
startOffset	Starting position of records to start query. Expects an integer.																
pageSize	Number of results to return. Expects an integer.																

Sample Response

```
[
  {
    "id": "4028e381697072b901697073acec0000",
    "username": "roleAnonymous",
    "appId": "appcenter",
    "appVersion": "1",
    "timestamp": "Mar 12, 2019 1:50:22 PM",
    "clazz": "org.joget.apps.workflow.security.WorkflowAuthenticationProvider",
    "method": "authenticate",
    "message": "Authentication for user admin (0:0:0:0:0:0:1) : true"
  },
  . . . . .
]
```