

Popup Select Box

Definition

Popup Select Box is an enhancement of the ordinary [SelectBox](#). Instead of selecting from a generic drop-down list, the **Popup Select Box** allows you to select from a [Datalist](#) instead.

Tips

If you have thousands of selections to choose from, **Popup Select Box** is an ideal form element to use as you will be choosing from listing with pagination and search filter, improving loading speed and user experience.



Figure 1: Screenshot showing Popup Select Box in Form Builder




Figure 2: Screenshot showing Popup Select Box in actual Form




Figure 3: Screenshot showing Popup Select Box in actual Form - Performing selection




Figure 4: Popup Select Box Properties

Name	Description
------	-------------

ID	Element ID (By declaring as "appeal_claim", a corresponding database table column "c_appeal_claim" will be created)
Label	Element Label to be displayed to end user.
Data List	Data List to display for selection.
Display Field	Field ID from the target Data List for eventual selected option label.

Advanced Options

Edit Popup Select Box > **Advanced Options**

Data

Default Value
Separate value with (;) if multiple values need to be set.

ID Field

Multiple Selection

URL Request Parameters for Datalist

	Parameter	Field Id	Default Value
+			

Validator

UI

Readonly

Display field as Label when readonly?

Select Button Label *

Popup Dialog Height



Popup Dialog Width

Workflow

Workflow Variable

Figure 5: Popup Select Box Properties - Advanced Options

Name	Description
Default Value	<p>Default Value when there's no existing value found/selected.</p> <p>Hash variable is accepted here. For example, you may key the following</p> <div style="border: 1px solid gray; padding: 5px; margin: 5px 0;"> <pre>#currentUser.firstName# #currentUser.lastName#</pre> </div> <p>to pre-populate the field with current logged in user's name.</p> <p>You may define multiple default options by separating them using semicolons.</p> <div style="border: 1px solid gray; padding: 5px; margin: 5px 0;"> <p>Sample</p> <pre>option1;option2;option3</pre> </div>
ID Field	<p>Target Data List's column ID value to be saved as option value.</p> <p>Default: id</p>
Multiple Selection	Toggle Multiple Selection.

URL Request Parameters for Datalist	Refine the target Data List selections by defining the filter criteria here. <table border="1" data-bbox="324 184 685 378"> <thead> <tr> <th>Name</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>Parameter</td> <td>Target Data List filter parameter name</td> </tr> <tr> <td>Field ID</td> <td>Current form element field ID</td> </tr> <tr> <td>Default Value</td> <td>Default Value for the search parameter</td> </tr> </tbody> </table>	Name	Description	Parameter	Target Data List filter parameter name	Field ID	Current form element field ID	Default Value	Default Value for the search parameter
Name	Description								
Parameter	Target Data List filter parameter name								
Field ID	Current form element field ID								
Default Value	Default Value for the search parameter								
Validator	Attach a Validator plugin to validate the input value. <div data-bbox="324 447 1482 562" style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"> <p> When will validation takes place?</p> <p>Validation will takes place whenever form is submitted except when it is submitted as "Save as Draft".</p> </div>								
Readonly	Determines if the element is editable.								
Display field as Label when readonly?	Displays the value of the element as plain text when element is set to "Readonly".								
Select Button Label	Select Button Label								
Popup Dialog Height	Height in character <div data-bbox="324 814 1482 951" style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"> <p>Sample</p> <p>500px</p> </div>								
Popup Dialog Width	Width in character <div data-bbox="324 1041 1482 1178" style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"> <p>Sample</p> <p>90%</p> </div>								
Workflow Variable	If the form is part of a workflow process, upon saving of the form (by clicking on "Save as Draft" or "Complete" button). The value in this input field will be saved into the corresponding workflow variable named here. <div data-bbox="324 1289 1482 1570" style="border: 1px solid #ccc; padding: 10px; margin-top: 10px;"> <p> Using a non-existent Workflow Variable name</p> <p>You will get the following warning with the name printed out (e.g. status) in the server log if you attempt to map to a non-existent Workflow Variable.</p> <div data-bbox="399 1402 1461 1499" style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <pre>context attribute status does not exist in process context - adding new attributes to the process context is not allowed</pre> </div> </div>								