

# Form Load/Options/Store Binder Plugin

- Usages
- Abstract Class
  - [org.joget.apps.form.model.FormBinder](#)
    - Field Detail
      - Constants
        - FORM\_LOAD\_BINDER
        - FORM\_OPTIONS\_BINDER
        - FORM\_STORE\_BINDER
      - Method Detail
        - Utility Methods
          - getElement
          - setElement
    - Interface
      - [org.joget.apps.form.model.FormLoadBinder](#)
        - Method Detail
          - Interface Methods
            - load
      - [org.joget.apps.form.model.FormLoadElementBinder](#)
      - [org.joget.apps.form.model.FormLoadMultiRowElementBinder](#)
      - [org.joget.apps.form.model.FormStoreBinder](#)
        - Method Detail
          - Interface Methods
            - store
        - [org.joget.apps.form.model.FormStoreElementBinder](#)
        - [org.joget.apps.form.model.FormStoreMultiRowElementBinder](#)
        - [org.joget.apps.form.model.FormLoadOptionsBinder](#)
        - [org.joget.apps.form.model.FormAjaxOptionsBinder](#)
          - Method Detail
            - Interface Methods
              - useAjax
              - loadAjaxOptions
          - [org.joget.apps.form.model.FormDataDeletableBinder](#)
            - Method Detail
              - Interface Methods
                - getFormId
                - getTableName
    - Plugin Properties Options
    - Tutorials
    - Related Community Plugins

## Usages

- **Form Load Binder Plugins** are used for extending the method of loading data in a form from any data source.
- **Form Options Binder Plugins** are used for extending the method of loading data in a form field's options from any data source.
- **Form Store Binder Plugins** are used for extending the method of storing data in a form to any data source.
- A useable Form Binder plugin must extends [org.joget.apps.form.model.FormBinder](#) abstract class and implements one or more of the corresponding interfaces.

## Abstract Class

### **org.joget.apps.form.model.FormBinder**

- Under wflow-core module
- Extended [org.joget.plugin.base.ExtDefaultPlugin](#). Please refer to [Plugin Base Abstract Class and Interface](#).
- Implemented [org.joget.plugin.property.model.PropertyEditable](#). Please refer to [Plugin Base Abstract Class and Interface](#).
- A base abstract class to develop a Form Load Binder, Form Options Binder or Form Store Binder plugin.

#### Field Detail

##### Constants

FORM\_LOAD\_BINDER

```
public static final java.lang.String FORM_LOAD_BINDER = "loadBinder";
```

Property key used in Form Field Element to retrieve Form Load Binder Plugin

```

FORM_OPTIONS_BINDER

public static final java.lang.String FORM_OPTIONS_BINDER = "optionsBinder";

Property key used in in Form Field Element to retrieve Form Options Binder Plugin

FORM_STORE_BINDER

public static final java.lang.String FORM_STORE_BINDER = "storeBinder";

Property key used in in Form Field Element to retrieve Form Sore Binder Plugin

```

#### **Method Detail**

##### Utility Methods

```

getElement

public org.joget.apps.form.model.Element getElement()

Gets the form field element which own this binder

setElement

public void setElement(org.joget.apps.form.model.Element element)

Sets the form field element which own this binder

```

#### Interface

##### **org.joget.apps.form.model.FormLoadBinder**

- Under wflow-core module
- A Form Load Binder loads data from a data source for use of an element and its children in a form.

#### **Method Detail**

##### Interface Methods

```

load

public org.joget.apps.form.model.FormRowSet load(org.joget.apps.form.model.Element element, java.lang.String primaryKey, org.joget.apps.form.model.FormData formData)

Loads data based on a primary key.

```

##### **org.joget.apps.form.model.FormLoadElementBinder**

- Under wflow-core module
- Used to mark a binder that loads data for an element e.g. form or section.
- Objects implementing this interface will be selectable in the Form Builder.
- No interface method is available in this interface

##### **org.joget.apps.form.model.FormLoadMultiRowElementBinder**

- Under wflow-core module
- Used to mark a binder that loads multi row data for an element e.g. Grid.
- Objects implementing this interface will be selectable in the Form Builder.
- No interface method is available in this interface

##### **org.joget.apps.form.model.FormStoreBinder**

- Under wflow-core module
- A Form Store Binder stores data from an element and its children into a data source.

#### **Method Detail**

##### Interface Methods

```

store

```

```
public org.joget.apps.form.model.FormRowSet store(org.joget.apps.form.model.Element element, org.joget.apps.form.model.FormRowSet rows, org.joget.apps.form.model.FormData formData)
```

Stores data in the data source.

#### **org.joget.apps.form.model.FormStoreElementBinder**

- Under wflow-core module
- Used to mark a binder that stores data for an element e.g. form or section.
- Objects implementing this interface will be selectable in the Form Builder.
- No interface method is available in this interface

#### **org.joget.apps.form.model.FormStoreMultiRowElementBinder**

- Under wflow-core module
- Used to mark a binder that store multi row data for an element e.g. Grid.
- Objects implementing this interface will be selectable in the Form Builder.
- No interface method is available in this interface

#### **org.joget.apps.form.model.FormLoadOptionsBinder**

- Under wflow-core module
- Extends [org.joget.apps.form.model.FormLoadBinder](#).
- Used to mark a binder that returns multiple options to populate a form element e.g. selectbox, checkbox, radio, etc.
- Each FormRow object return by FormRowSet object should contains key "value" and "label".

#### **org.joget.apps.form.model.FormAjaxOptionsBinder**

- Under wflow-core module
- This interface indicate that a Form Options Binder support retrieving options using AJAX
- Must use together with [org.joget.apps.form.model.FormLoadOptionsBinder](#).
- Each FormRow object return by FormRowSet object should contains key "value" and "label".

#### **Method Detail**

##### Interface Methods

useAjax

```
public boolean useAjax()
```

Use to decide this field is using AJAX to load its options or not.

loadAjaxOptions

```
public org.joget.apps.form.model.FormRowSet loadAjaxOptions(java.lang.String[] dependencyValues);
```

Retrieve options based on dependency values

#### **org.joget.apps.form.model.FormDataDeletableBinder**

- Under wflow-core module
- This interface indicate that the form data load by Form Load Binder is deletable from Form Data table.

#### **Method Detail**

##### Interface Methods

getFormId

```
public java.lang.String getFormId()
```

Get Form Id of the loaded data.

getTableName

```
public java.lang.String getTableName()
```

Get table name of the loaded data.

## Plugin Properties Options

- Please refer to [Plugin Properties Options](#) for more information.

## Tutorials

- [Guideline for developing a plugin](#)
- [How to develop a JDBC Options Binder](#)
- [How to develop a JDBC Form Load Binder](#)
- [How to develop a JDBC Form Store Binder](#)
- [File Upload Form Element Integrated with Amazon S3](#)

## Related Community Plugins

- **Bean Shell Form Binder**  
org.joget.apps.form.lib.BeanShellFormBinder (wflow-core)
- **Default Form Binder**  
org.joget.apps.form.lib.DefaultFormBinder (wflow-core)
- **Workflow Form Binder**  
org.joget.apps.form.lib.WorkflowFormBinder (wflow-core)