

ResourceBundleUtil

- [Description](#)
- [Code Sample](#)
- [Methods](#)
 - [getApplicationContext](#)
 - [getMessage](#)
 - [getMessageSource](#)
 - [getResourceBundleMessageDao](#)
 - [getSetupApplicationContext](#)
 - [POFileImport](#)

Description

- [org.joget.commons.util.ResourceBundleUtil](#)
- Under wflow-core module
- Utility class to retrieve plugin propertise value and i18n message

Code Sample

```
import org.joget.commons.util.ResourceBundleUtil;

String label = ResourceBundleUtil.getMessage("general.method.label.ok");
```

Methods

- getApplicationContext
- ```
public static org.springframework.context.ApplicationContext getApplicationContext()
```
- Utility method to retrieve the ApplicationContext of the system
- getMessage
- ```
public static java.lang.String getMessage(java.lang.String code)
```
- Gets the i18n message based on code
- getMessage
- ```
public static java.lang.String getMessage(java.lang.String code, java.lang.Object[] args)
```
- Gets the i18n message with arguments based on code
- getMessage
- ```
public static java.lang.String getMessage(java.lang.String code, java.lang.Object[] args, java.lang.String defaultMessage)
```
- Gets the i18n message with arguments based on code
- Return** default message if i18n message not found
- getMessage
- ```
public static java.lang.String getMessage(java.lang.String code, java.lang.String defaultMessage)
```
- Gets the i18n message based on code
- Return** default message if i18n message not found
- getMessage

```
public static java.lang.String getMessage(java.lang.String code, java.util.Locale locale)

 Gets the i18n message based on code and locale

getMessage

public static java.lang.String getMessage(java.lang.String code, java.lang.Object[] args, java.util.Locale locale)

 Gets the i18n message with arguments based on code and locale

getMessage

public static java.lang.String getMessage(java.lang.String code, java.lang.String defaultMessage, java.util.Locale locale)

 Gets the i18n message based on code

Return default message if i18n message not found

getMessage

public static java.lang.String getMessage(java.lang.String code, java.lang.Object[] args, java.lang.String defaultMessage, java.util.Locale locale)

 Gets the i18n message with arguments based on code and locale

Return default message if i18n message not found

getMessageSource

public static org.springframework.context.support.MessageSourceAccessor getMessageSource()

 Gets the message source

getResourceBundleMessageDao

public static org.joget.commons.spring.model.ResourceBundleMessageDao getResourceBundleMessageDao()

 Method used by the system to get resource bundle message dao

getSetupApplicationContext

public static org.springframework.context.ApplicationContext getSetupApplicationContext()

 Utility method to retrieve the Setup ApplicationContext of the system

POFileImport

public static void POFileImport(org.springframework.web.multipart.MultipartFile multipartFile, java.lang.String locale) throws java.io.IOException

 Method used to import message from PO file
```