Bean Shell Action

- Introduction
- Bean Shell Action Properties
 - O Configure Bean Shell Datalist Action
 - O Visibility Control

Introduction

Bean Shell Action allows you to write custom Java code to perform custom actions on the datalist.

Bean Shell Action Properties

Configure Bean Shell Datalist Action




Figure 1: Bean Shell Action Menu




Figure 2: Bean Shell Action Properties

| Name | Description | | | |
|----------------------|---|--|--|--|
| Label | Link / Button label. | | | |
| Confirmation Message | Confirmation message before performing action. | | | |
| Script | Script in Java. | | | |
| | See: | | | |
| | Bean Shell Programming Guide - Datalist Action Utility and Service Methods. | | | |

Visibility Control




Figure 3: Visibility Control Properties

| Name | Description | | | | |
|-------|--|---|--|--|--|
| Rules | Defines when the action should appear based on the condition(s) set. | | | | |
| | Only applicable to row action placeholder. | | | | |
| | Field | Description | | | |
| | Join Type | Condition type to fulfill. | | | |
| | Field | Form field ID. | | | |
| | Operator | Available operator types: | | | |
| | | Equal Not Equal Greater Than Greater Than Or Equal Less Than Less Than Or Equal Like Not Like In Not In Is True Is False Is Empty Is Not Empty Regex Not Regex | | | |
| | Value | Show the action when form field matches the condition. | | | |