# Date Picker

- Introduction
- Get Started
- Date Picker Properties
  - O Configure Date Picker
    - O Advanced Options
      - Data
      - Validation
      - UI
      - Workflow
- Date Formatting Based On Locale
- Display Date Time Based On Coordinated Universal Time (UTC)

#### Introduction

Date Picker extends the capability of a normal text field with a date picker library.

### Get Started

The easiest way to see how the Date Picker works is to use the existing built-in App Expenses Claims. Here are the steps:

- 1. Start the Joget Server and open the App Center.
- 2. Log in as **admin** and click on the pencil icon on the **Expenses Claim** to open the **App Composer**. (see Figure 1)



3. Click on Expense Claim Entry and you will be directed to the Form Builder.

4. Click on the Date Picker element on the canvas to open up the Date Picker properties. (see Figure 2)

A Expenses Claim v1 (Pu	olished) 0	R	- Form	Expenses Claim v1: Expense Approval Entry (Published)	🕴 Generate App 🕜 Save
	<b>B</b>		Builder	🗶 Design 象 Settings 🕲 Proview 💩 🗉 合 68 🗏 昭 〇 ド () 回 🕴 🥎 이 가	
			Search Palette		×
Search	@ Show	в	Toggle Switch	claim	B Properties O Styles
Tags		⊞	Radio	uzantusta admin bita	Search Properties
Form Builder	$\odot$	Q	🛱 Data Ricker	Doze Proter 1 1 4 B	Configure Date Picker 🛛 🔍 🎱
Expense Approval Detail	Lespense_claim	$\mathcal{T}_{\mathcal{T}}$		Date Picker MM/DD/YYY	Label*
		8	The Upload	Approver Admin Admin	Date
Expense Approval Entry	j_espense_opproval	P	Subform	Approver remark	ID *
Expense Approval Form	j_espense_claim				date
Execute Chim Entry		0	Star Bating	ApprovedDate 2022-09-06 🗞	Allow Manual Input
Diperse carrie bioly		8		ApprovedBy Admin Admin 🗞	Field Type
Expense Claim Form	j_expense_claim		He Grid		
Expense Claim New	Lexpense_claim	ø	Custom HTML		
		S	ID ID Generator		Advanced Options
Expense Claim Resubmit	juliana una		Enterprise v		S DATA
Expense Claim View	Lespense_claim				Default Value
Expense Finance Form	j_expense_claim		multi raged Form		Data Format
			Multi Select Box		yyyy-MM-dd
Expense Setup Category	j_expense_col		Popup Select Box		• 14110-1701
Popup Select Box	text_area		Calculation Field		* VALUATION
					Validator

Figure 2

5. Click on **Preview** and click on the Date Picker to see it in action.

## Date Picker Properties

Configure Date Picker

Configure Date Picker 😧	⊗
Label *	
Date	
ID *	
date	
Allow Manual Input	
Field Type	
Date only	~

Name	Description
Label	Element Label to be displayed to the end-user.
ID	Element ID (By declaring as "date", a corresponding database table column "c_date" will be created)
	Please see Form Element for more information about defining the ID and list of reserved IDs.
Allow Manual Input	Rather than using the calendar picker, a user may key in the date directly if checked.

Field Type	New date picker property to define the field type as:		
	Date Only     Date and Time		
	Date and Time Stored In UTC		
	Time Only		

Advanced Options

Data

Advanced Options	♥
S DATA	
Default Value	
Data Format 😯	
yyyy min dd	

Name	Description		
Default Value	Default Value when there's no existing value found/selected.		
	The hash variable is accepted here. For example, you may key the following		
	#date.dd-MM-yyyy#		
	Date Format Date format defined here should follow Data Format.		
Data Format	The Data Format uses the Java date syntax. For example, the yyyy-MM-dd displays as 2019-10-23.		
	Reference: https://github.com/phstc/jquery-dateFormat		

Validation

Validator	
	~
Start Date Field ID	
	~
End Date Field ID	
	~
Set Current Date As	
	~

Name	Description	
Validator	Attach a Validator plugin to validate the input value. Please see Form Validator.	
	() When will validation takes place?	
	Validation will take place whenever a form is submitted except when it is submitted as "Save as Draft".	
Start Date Field ID	This option should be used in conjunction with "Set Current Date As".	
End Date Field ID	This option should be used in conjunction with "Set Current Date As".	
Set Current Date As	Choices of:-	
	• Minimum Date	
	Maximum Date	

UI

S UI	
Placeholder	
Display Format 🕜	
Date Picker Year Range *	
c-10:c+10	
Readonly	
Display Field as Label When Readonly?	

Name	Description		
Placeholder	The placeholder attribute specifies a short hint that describes the expected value of an input field (e.g. a sample value or a short description of the expected format). The short hint is displayed in the input field before the user enters a value.		
Display Format	The Display Format uses the jQuery date syntax. For example, the yy-M-dd displays as 2019-10-23. Reference: https://github.com/phstc/jquery-dateFormat		
	When this field is left empty, the following will be considered.		
	<ol> <li>If current locale starts with "zh", the format will be set as "yy-mm-dd".</li> <li>If "Using Locate Date Format" is set in General Settings, date format based on current user's locale will be used.</li> <li>Otherwise, it will use "M/dd/yy".</li> </ol>		
Date Picker Year Range	Range of years to be shown		
	In essence, the value left of the colon "." must be a negative number and on the right must be a positive number. It indicates to Joget Workflow how many years earlier and how many years forward to display in the year select box based on the selected year.		
	A value of "c-0:c+0" is also valid, this indicates to the user that he cannot change the year value (it will default to the current system year).		
	Sample - Show 10 years before and after		
	c-10:c+10		
	Sample - Show specific year range		
	2000:2020		
Readonly	Determines if the element is editable.		
Display field as Label when readonly?	Displays the value of the element as plain text when element is set to "Readonly".		

S WORKFLOW	
Workflow Variable	

Name	Description	n			
Workflow Variable	If the form is part of a workflow process, upon saving of the form (by clicking on "Save as Draft" or "Complete" button). The value in this input field will be saved into the corresponding workflow variable named here.				
	0	Using a non-existent Workflow Variable name You will get the following warning with the name printed out (e.g. status) in the server log if you attempt to map to a non-existent Workflow Variable.			
		context attribute status does not exist in process context - adding new attributes to the process context is not allowed			

### Date Formatting Based On Locale

Here are the steps to set the Date Picker to automatically display the date format based on user locale (for example "MM/dd/yyyy" for "en\_US" locale ):

1. In System Settings:

- ${\bf a.}\,$  Tick the checkbox 'Using Locale Date Format'.
- **b.** Leave the `System Date Format` field blank or empty.
- ${\bf c}_{\text{-}}$  Tick the checkbox `Enable User Locale Selection`.
- d. Enter into the 'User Locale Options' field the locales allowed, for example "de,en\_US".
- e. Save the System Settings.
- 2. In your "Form Builder > Date Picker", leave the 'Display Format' property blank or empty.
- 3. User logs in, sets his locale in 'My Profile'. Date Picker field will show the date format as per his/her locale.

### Display Date Time Based On Coordinated Universal Time (UTC)

You can 'force' Joget to generate the date time from the data hash variable based on UTC, by adding the parameter "-Duser.timezone=UTC" in the JAVA\_OPTS variable in the Joget startup script/batch file:

set JAVA\_OPTS=-Xmx2048M -Dwflow.home=./wflow/ -javaagent:./wflow/aspectjweaver-1.8.5.jar -Duser.timezone=UTC javaagent:./wflow/glowroot/glowroot.jar