

Select Box

- [Introduction](#)
- [Get Started](#)
- [Select Box Properties](#)
 - [Configure Select Box](#)
 - [Advanced Options](#)
 - [Data](#)
 - [Dependency](#)
 - [UI](#)
 - [Workflow](#)

Introduction

Select Box is one of the generic HTML Form input elements. In the Form Builder, one is able to define the options available to the Select Box via various means, including with the use of [Form Options Data Store](#)

Get Started

The easiest way to see how the Select Box works is to create a new app. Here are the steps:

1. Start the **Joget Server** and open the **App Center**.
2. Log in as admin and click on the pencil icon on the **Expenses Claim** to open the **App Composer**. (see Figure 1)




Figure 1

3. Under **For Builder** column, click on **Expense Claim Entry** (see Figure 2).




Figure 2

4. Drag and drop a **Select Box** element on to the canvas.
5. **Click** on the **Select Box** element to open up the Configure Select Box properties.
6. Fill up the following fields as follows and click on **Apply Change** (see Figure 3):
 - a. ID: **type**
 - b. Options (Hardcoded):

| Default Value | Label |
|---------------|---------------|
| Local | Local |
| International | International |




Figure 3

7. Click on **Preview**, click on the options available in the **country** field.

Select Box Properties

Configure Select Box

Configure Select Box ?

Label

Select Box



ID *

field2

Options


| VALUE | LABEL | GROUPING |
|---------------|---------------|----------|
| | | |
| local | Local | |
| international | International | |


Or Load Data From

| Name | Description |
|---------------------|---|
| Label | Element Label to be displayed to the end-user. |
| ID | <p>Element ID (By declaring as "country", a corresponding database table column "c_country" will be created)</p> <p>Please see Form Element for more information about defining the ID and list of reserved IDs.</p> |
| Options (Hardcoded) | <p>Select Box options</p> <div>  Options defined here will not be put into use if Options Binder is defined below. </div> |
| Or Load Data From | <p>Options to be populated dynamically using Options Binder plugin.</p> <div>  Performance Warning <p>If you have thousands of select options or sourcing them from Options Binder, this may cause a significant increase in page load time. Consider using Popup Select Box instead.</p> </div> |

Advanced Options


Data

 DATA


Value 

☐ Multiple Selection

Validator

| Name | Description |
|--------------------|---|
| Value | <p>Default Value when there's no existing value found/selected.</p> <p>A hash variable is accepted here. For example, you may key the following</p> <div>#currentUser.firstName# #currentUser.lastName#</div> <p>to pre-populate the field with currently logged in user's name.</p> <p>You may define multiple default options by separating them using semicolons.</p> <div><div>Sample</div><div>option1;option2;option3</div></div> |
| Multiple Selection | <p>Toggle Multiple Selection.</p> |
| Validator | <p>Attach a Validator plugin to validate the input value.</p> <div><div> When will validation takes place?</div><div>Validation will take place whenever a form is submitted except when it is submitted as "Save as Draft".</div></div> <p>Available Options:</p> <ul style="list-style-type: none">• Basic• BeanShell• Data and Time Duplicate Validator• Directory• Duplicate Value• Equal Value• Multi Form Validator• Password• Plugin Template - Validator |

Workflow Variable

| Name | Description |
|-------------------|---|
| Workflow Variable | <p data-bbox="240 506 1487 552">If the form is part of a workflow process, upon saving of the form (by clicking on "Save as Draft" or "Complete" button). The value in this input field will be saved into the corresponding workflow variable named here.</p> <div data-bbox="245 575 1482 827"><div data-bbox="261 596 293 632"></div><div data-bbox="310 596 589 621">Using a non-existent Workflow Variable name</div><p data-bbox="313 642 1219 665">You will get the following warning with the name printed out (e.g. status) in the server log if you attempt to map to a non-existent Workflow Variable.</p><div data-bbox="318 686 1463 785"><pre data-bbox="328 701 1395 751">context attribute status does not exist in process context - adding new attributes to the process context is not allowed</pre></div></div> |