LDAP Directory Manager

The $\ensuremath{\mathsf{LDAP}}$ $\ensuremath{\mathsf{Directory}}$ $\ensuremath{\mathsf{Manager}}$ allows you to integrate Joget with your existing AD/LDAP server.

As opposed with the earlier version, the enhanced LDAP Directory Manager implements all methods on the Joget Directory Manager class. In other words, it has been made possible to list and navigate through user, department and group entities in Joget itself.




Figure 1: Configure LDAP Directory Manager



Important

Do not lock yourself out when you are configuring any Directory Manager plugin. Keep your browser session open and perform actual test in other machine/browser so that in case of any wrong configurations



User License

User license determines how many eventual users (sorted alphabetically) from your LDAP/AD can login to the system. Make sure that you configure the plugin accordingly.

Sample Configuration

Configure LDAP Directory Manager

Name	Value
URL	Idap://IP_ADDRESS:389 Idaps://IP_ADDRESS:636
Admin Username (Principal)	cn=admin,dc=joget,dc=org
Admin Password (Credential)	admin
Root DN	DC=joget,DC=org



Administrative Access

In case you have a misconfiguration and cannot login, you can make use of the credential set above (Admin Username (Principal) & Admin Password (Credential)) to login as the administrator.

Value Name User Base DN User Base DN (i) Tips If you set the "User Base DN" to your LDAP Root DN, it means that the search will start from the Root DN until it finds all the results that matched the search filter. So, setting the "User Base DN" precisely is very important as it will decide where the search is starting from. It will save all the unnecessary search between the Root DN to your " Root DN DC=joget,DC=org Under the Root DN, you have the following DN: DC=HR,DC=joget,DC=org DC=Product Department, DC=joget, DC=org DC=Operation, DC=joget, DC=org DC=Users,DC=joget,DC=org If your users are all under "DC=Users,DC=joget,DC=org", you should set this to "User Base DN". By doing this, it will not go through all the other entries and it's child entries before reaching "DC=Users,DC=joget,DC=org". (objectClass=person) User Import Search Filter (i) Tips Value (&(objectClass=person)(|(cn=admin)(cn=cat)(cn=jack)(cn=john)(cn=jackie))) This mean all the LDAP entries which have "objectClass" attribute equals to "person" and "cn" attribute equals to either "admin", "cat", "jack", "john" or "jackie" are Joget users. So, when a login is performed by "admin", the search filter will add additional filter and become "(&(&(objectClass=personX|(cn=adminXcn=catX(cn=jackX(cn=john)(cn=jackie))) You will notice an extra (cn=admin) is added to the search filter to make sure it return only the "admin" user. User License User license determines on how many eventual users (sorted alphabetically) from your LDAP/AD can log in into the system. You can make use of this attribute to control amount of users returned from your LDAP. Attribute Mapping -Username Attribute Mapping - First givenName Attribute Mapping - Last sn Attribute Mapping - Email

Attribute Mapping - Status	
Attribute Mapping - Time Zone	8
Attribute Mapping - Locale	en_US

Employment

Name	Value
Attribute Mapping - Employee Code	
Attribute Mapping - Job Title	
Attribute Mapping - Report To	
Map To "Report To" Entry Attribute	
Attribute Mapping - Groups	
Map To LDAP Group Entry Primary Attribute	dn
Attribute Mapping - Departments	
Map To LDAP Department Entry Primary Attribute	dn
Attribute Mapping - Grade	
Map To LDAP Grade Entry Primary Attribute	dn

Group

Name	Value
Group Base DN	
Group Import Search Filter	(objectClass=groupOfNames)
Attribute Mapping - ID	cn
Attribute Mapping - Name	description
Attribute Mapping - Description	description
Attribute Mapping - Users	member
Map To LDAP User Entry Primary Attribute	dn

Department

Name	Value
Department Base DN	
Department Import Search Filter	(objectClass=groupOfNames)
Attribute Mapping - ID	cn
Attribute Mapping - Name	description
Attribute Mapping - Description	description
Attribute Mapping - HOD	owner
Attribute Mapping - Users	member
Map To LDAP User Entry Primary Attribute	dn

Grade

Name	Value
Grade Base DN	
Grade Import Search Filter	
Attribute Mapping - ID	
Attribute Mapping - Name	
Attribute Mapping - Description	
Attribute Mapping - Users	
Map To LDAP User Entry Primary Attribute	

Admin Role

Name	Value
Admin Role Base DN	
Admin Role Import Search Filter	(&(objectClass=person)(cn=admin))
Attribute Mapping - Users	cn
Map To LDAP User Entry Primary Attribute	dn

Advanced

Name	Value
Result Size Per Paged Search	100
Debug Mode	Checked Tips The Debug Mode is highly recommended to be turned on when configuring the LDAP plugin for the first time. When debug mode is on, you can find all the search queries performed by the directory manager. They will all be logged into the log file. From there, you can observe the search filter string and improve the accuracy and performance of the lookup.