

Sample JSON API Integration

- [Start a Process](#)
- [Complete the Assignment with Variables](#)
- [Abort a Process](#)

Assume that the process definition id is CRM#1:newpkg1_wp1, the username & password is admin, and the base URL of <http://localhost:8080/jw/>.

Start a Process

By using JSON API [/json/workflow/process/start/\(*:processDefId\)](/json/workflow/process/start/(*:processDefId))



Method Call

Please note that one must use POST to make such particular JSON API call.

Sample Call:

```
/web/json/workflow/process/start/CRM:1:newpkg1_wp1?j_username=admin&j_password=admin
```

Sample Result:

```
{ "activityId": "2122_2117_CRM_newpkg1_wp1_newpkg1_wp1_act1", "processId": "2117_CRM_newpkg1_wp1" }
```

NOTE: workflow variables can be set when starting a process by passing additional parameters into the URL, e.g., `var_ticketId=123456&var_relatedTo=network`.

Complete the Assignment with Variables

By using JSON API [/json/workflow/assignment/completeWithVariable/\(*:activityId\)](/json/workflow/assignment/completeWithVariable/(*:activityId))



Method Call

Please note that one must use POST to make such particular JSON API call.

Sample Call:

```
/web/json/workflow/assignment/completeWithVariable/2122_2117_CRM_newpkg1_wp1_newpkg1_wp1_act1?  
var_ticketId=123456&var_relatedTo=network&j_username=admin&j_password=admin
```

Sample Result:

```
{ "activityId": "2122_2117_CRM_newpkg1_wp1_newpkg1_wp1_act1", "assignment": "org.joget.workflow.model.  
WorkflowAssignment@1b99f74", "processId": "2117_CRM_newpkg1_wp1", "status": "completed" }
```

Abort a Process

By using JSON API [/json/workflow/process/abort/\(*:processId\)](/json/workflow/process/abort/(*:processId))



Method Call

Please note that one must use POST to make such particular JSON API call.

Sample Call:

```
/web/json/workflow/process/abort/2117_CRM_newpkg1_wp1?j_username=admin&j_password=admin
```

Sample Result:

```
{"id":"2117_CRM_newpkg1_wp1","status":"aborted"}
```