

System

Definition

System API can interact with configuration values in Joget [General Settings](#).

System

☐ Find Setting

☐ Update Setting

☐ Get Setting

- Find Setting
- Get Setting
- Update Setting

	Name	Description																						
1	Find Setting	<div>Get all settings and its values by default.</div> <div>Able to filter or sort the returned results via parameters.</div>																						
		<table><tr><th>Name</th><th>Description</th></tr><tr><td>URL</td><td>/system/find</td></tr><tr><td>HTTP Method</td><td>GET</td></tr><tr><td>Query String Parameters</td><td><table><tr><th>Parameter</th><th>Description</th></tr><tr><td>propertyFilter</td><td>Filters the response via property ID.</td></tr><tr><td>sort</td><td>Settings data column to sort. Must be used in conjunction with "sortDescending" parameter.</td></tr><tr><td>sortDescending</td><td>Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.</td></tr><tr><td>startOffset</td><td>Starting position of records to start query. Expects an integer.</td></tr><tr><td>pageSize</td><td>Number of results to return. Expects an integer.</td></tr></table></td></tr><tr><td>Sample Response</td><td><pre>[{ "property": "css", "value": "" }, { "property": "smtpPort", "value": "" }, { "property": "criticalWarningLevel", "value": "" }, ]</pre></td></tr></table>	Name	Description	URL	/system/find	HTTP Method	GET	Query String Parameters	<table><tr><th>Parameter</th><th>Description</th></tr><tr><td>propertyFilter</td><td>Filters the response via property ID.</td></tr><tr><td>sort</td><td>Settings data column to sort. Must be used in conjunction with "sortDescending" parameter.</td></tr><tr><td>sortDescending</td><td>Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.</td></tr><tr><td>startOffset</td><td>Starting position of records to start query. Expects an integer.</td></tr><tr><td>pageSize</td><td>Number of results to return. Expects an integer.</td></tr></table>	Parameter	Description	propertyFilter	Filters the response via property ID.	sort	Settings data column to sort. Must be used in conjunction with "sortDescending" parameter.	sortDescending	Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.	startOffset	Starting position of records to start query. Expects an integer.	pageSize	Number of results to return. Expects an integer.	Sample Response	<pre>[{ "property": "css", "value": "" }, { "property": "smtpPort", "value": "" }, { "property": "criticalWarningLevel", "value": "" }, ]</pre>
		Name	Description																					
		URL	/system/find																					
		HTTP Method	GET																					
		Query String Parameters	<table><tr><th>Parameter</th><th>Description</th></tr><tr><td>propertyFilter</td><td>Filters the response via property ID.</td></tr><tr><td>sort</td><td>Settings data column to sort. Must be used in conjunction with "sortDescending" parameter.</td></tr><tr><td>sortDescending</td><td>Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.</td></tr><tr><td>startOffset</td><td>Starting position of records to start query. Expects an integer.</td></tr><tr><td>pageSize</td><td>Number of results to return. Expects an integer.</td></tr></table>	Parameter	Description	propertyFilter	Filters the response via property ID.	sort	Settings data column to sort. Must be used in conjunction with "sortDescending" parameter.	sortDescending	Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.	startOffset	Starting position of records to start query. Expects an integer.	pageSize	Number of results to return. Expects an integer.									
		Parameter	Description																					
		propertyFilter	Filters the response via property ID.																					
		sort	Settings data column to sort. Must be used in conjunction with "sortDescending" parameter.																					
		sortDescending	Sort the specified "sort" parameter value in ascending or descending order. Expects a boolean value. Must be used in conjunction with "sort" parameter.																					
startOffset	Starting position of records to start query. Expects an integer.																							
pageSize	Number of results to return. Expects an integer.																							
Sample Response	<pre>[{ "property": "css", "value": "" }, { "property": "smtpPort", "value": "" }, { "property": "criticalWarningLevel", "value": "" }, ]</pre>																							

2

Get Setting

Get the value of a setting.

Name	Description				
URL	/system/{property}				
HTTP Method	GET				
Path Parameters	<table><tr><th>Parameter</th><th>Description</th></tr><tr><td>property</td><td>Property ID.</td></tr></table>	Parameter	Description	property	Property ID.
Parameter	Description				
property	Property ID.				
Sample Response	<pre>{ "property": "defaultUserview", "value": "appcenter/v"}</pre>				

3

Update Setting

Update the value of a setting.

Name	Description						
URL	/system						
HTTP Method	PUT						
Body Parameters	<table><tr><th>Parameter</th><th>Description</th></tr><tr><td>property</td><td>Property ID.</td></tr><tr><td>value</td><td>Property value.</td></tr></table>	Parameter	Description	property	Property ID.	value	Property value.
Parameter	Description						
property	Property ID.						
value	Property value.						
Sample Response	<pre>{ "property": "disablePerformanceAnalyzer", "value": "true"}</pre>						