

Calendar Menu

- Introduction
- Calendar Menu Properties
 - Configure Calendar Menu
 - Column to Data Mappings
 - Advanced
 - Google Calendar Integration
 - Events & UI
 - Performance & Offline
 - Cache Settings
 - PWA Offline Settings
- Download Demo App

Introduction

The **Calendar Menu** displays records from your preferred datalist as calendar events, in formats of day/week/month in your app's userview.

1. For this to work, you must map the **form** and **field IDs** that stores the calendar records, into the Calendar plugin properties page.
2. The Calendar Menu also supports Google API to display your preferred country's public holidays in the calendar.
See [Google Calendar Integration](#) for more details.

To know more about Calendar Menu, do check out the [sample apps here](#).

Calendar Menu Properties

Configure Calendar Menu

The screenshot shows a configuration window titled "Configure Calendar Menu" with a breadcrumb trail: "Configure Calendar Menu > Column to Data Mappings > Advanced > Performance & Offline". The form contains the following fields:

- Id:** 6E7AD0BA93DC4DA5A2C9E6F87F1094E0
- Custom ID:** (empty text input)
- Label *:** Calendar View
- Page Title:** (empty text input)
- Data Binder *:** (empty dropdown menu)
- Auto Handle Date Range?** :

Figure 1: Calendar Menu Properties

Name	Description
id	Menu element unique id. Userview will use this id in the URL for the menu if the Custom ID is empty.
Custom ID	Item link slug. Optional field. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> Ensure that value defined here is unique to other userview menus in the app, since the first matching/conflicting ID will take precedence in page loading.</div>
Label	The userview menu label.

Page Title	Calendar page title.
Data Binder	See list of available Datalist Binders , to source the data for calendar entries.
Auto Handle Date Range	<p>Enable this option to automatically handle range of calendar events to be populated into the calendar, based on event dates and calendar view format.</p> <p>If this option is disabled, you need to manually handle date range via <code>#requestParam.start#</code> and <code>#requestParam.end#</code> request parameter hash variables in your datalist binder configuration.</p> <p>Date format for date range is <code>yyyy-MM-dd</code>.</p>

☰ CALENDAR MENU
🏠 0

[Home](#) / [Manage Event](#) / [Display Calendar View](#)

Display Calendar View

My Google Calendar

<
>
Today

March 2017

Month
Week
Day

Sun	Mon	Tue	Wed	Thu	Fri	Sat
26	27	28	1	2	3	4
5	6 Go to seminar A	7	8	9	10	11
12	13	14	15	16	17	18
19	20	21	22	23	24	25
26	27	28	29	30	31	1
2	3	4	5	6	7	8

Figure 2: Sample Calendar Menu in runtime

Column to Data Mappings

+
Auto save when close?
×

Column to Data Mappings ⊞

Configure Calendar Menu > **Column to Data Mappings** > Advanced > Performance & Offline

Event ID (column ID)

Event Title (column ID) *

All Day (column ID, boolean value)

From Date (column ID) *

From Time (column ID)

To Date (column ID)

To Time (column ID)

Date Format *

Time Format

Event Url (column ID)

Color (column ID)

CSS Class (column ID)

Additional Data

NAME	COLUMN ID
+	

< Prev
Next >

OK
Cancel


Figure 3: Column to Data Mappings Properties

Name	Description
Event ID (column ID)	Defines individual calendar entry IDs, based on each distinct datalist record.
Event Title (column ID)	Calendar entry title.
All Day (column ID, boolean value)	Expects a <i>true</i> or <i>false</i> value, to determine if the calendar entry is an all day event.
From Date (column ID)	Calendar entry start date value. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> i You can also point to Date Picker form field with time support. </div>
From Time (column ID)	Calendar entry start time value. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> i If the From Date value already contains a time value, leave this field empty. </div>

To Date (column ID)	<p>Calendar entry end date value.</p> <p> You can also point to Date Picker form field with time support.</p>
To Time (column ID)	<p>Calendar entry end time value.</p> <p> If the To Date value already contains a time value, leave this field empty.</p>
Date Format	<p>You must specify the actual date format used by the From/To Date values.</p> <p>Date Format in Java is expected here, e.g.: yyyy-MM-dd.</p> <p> If the date values has a time value, just define the date format only and not the time format.</p> <p>Because the time format is already handled by the Time Format property.</p>
Time Format	<p>Available options:</p> <ul style="list-style-type: none"> • 24 Hour System (e.g: 18:00) • 12 Hour System (e.g: 6:00 PM)
Event Url (column ID)	Calendar entry URL.
Color (column ID)	Calendar entry CSS color code to style the calendar event.
CSS Class (column ID)	Calendar entry CSS class to style the calendar event.
Additional Data	Any additional data to be added to the calendar entry.

Advanced

Google Calendar Integration



Advanced

Configure Calendar Menu > Column to Data Mappings > **Advanced** > Performance & Offline

Google Calendar Integration

Additional Data

GOOGLE CALENDAR API KEY	CALENDAR ID	CSS CLASSES	COLOR
-------------------------	-------------	-------------	-------

Figure 4: Google Calendar Integration Properties

Name	Description
------	-------------

Additional Data

Configurations to load calendar entries from Google Calendar.

Notes if you want the Calendar Menu plugin to connect to Google Calendar:

1. Every request your application sends to the Google Calendar API must include an authorization token.

The token also identifies your application to Google.

Here are the steps to obtain the Google Calendar API Key:

- Go to the [Google Developer Console](#) and create a new project (it might take a second).
- Once in the project, go to APIs & auth > APIs on the sidebar.
- Find "Calendar API" in the list and turn it ON.
- On the sidebar, click APIs & auth > Credentials.
- In the "Public API access" section, click "Create new Key".
- Choose "Browser key".
- If you know what domains will host your calendar, enter them into the box. Otherwise, leave it blank. You can always change it later.
- Your new API key will appear. It might take second or two before it starts working.
- Copy and paste your API key into the Calendar menu properties "Configure Calendar Menu>Data Binder>Advanced" page.

2. Steps to enable your Google Calendar to be public:

- In the Google Calendar interface, locate the "My calendars" area on the left.
- Hover over the calendar you need and click the downward arrow.
- A menu will appear. Click "Calendar Settings".
- Check "Make this calendar public".
- Make sure "Share only my free/busy information" is unchecked.
- Click "Save".
- Obtain your Google Calendar's ID:
 - In the Google Calendar interface, locate the "My calendars" area on the left.
 - Hover over the calendar you need and click the downward arrow.
 - A menu will appear. Click "Calendar settings".
 - In the "Calendar Address" section of the screen, you will see your Calendar ID. It will look something like "**abcd1234@group.calendar.google.com**".
- Copy and paste your API key into the Calendar menu properties "Configure Calendar Menu>Data Binder>Advanced" page.
- You can read more at [Google Calendar API](#) site.


Events & UI

Events & UI	
Event Rendering Callback (Javascript)	1 <code>//console.log(event); console.log(element); console.log(view);</code>
Event After Rendering Callback (Javascript)	1 <code>//console.log(event); console.log(element); console.log(view);</code>
Event After All Rendering Callback (Javascript)	1 <code>//console.log(view);</code>
Event Click Callback (Javascript)	1 <code>//console.log(event); console.log(jsEvent); console.log(view);</code>
Time Display Format ?	
Custom Header (HTML)	1
Custom Footer (HTML)	1

Figure 5: Events & UI Properties


Name	Description
------	-------------

Event Rendering Callback (Javascript)	Custom Javascript code to execute upon rendering each calendar event.
Event After Rendering Callback (Javascript)	<p>Custom Javascript code to execute for each calendar event, after it has been rendered.</p> <div data-bbox="435 226 1484 296" style="background-color: #f0f0f0; padding: 5px;">Sample Code to change the event time indicator to a more meaningful value</div> <pre data-bbox="444 310 1474 499"> var fromTime = event.start.format("H:mm").toString(); var toTime = event.end.format("H:mm").toString(); if (fromTime.indexOf("10:00") > -1 && toTime.indexOf("16:20") > -1) { \$(element).find('span.fc-time').text("First Shift --> "); } </pre> <p data-bbox="435 520 1484 548">See sample app here for more info: APP_calendarTest-sample.jwa</p>
Event After All Rendering Callback (Javascript)	<p>Custom JavaScript code to execute after all rendering of the calendar menu has been completed.</p> <p>In the sample below, upon clicking on a calendar date, it will redirect to an event form and prepopulate a date field with the clicked date.</p> <div data-bbox="435 657 1484 726" style="background-color: #f0f0f0; padding: 5px;">Sample Code</div> <pre data-bbox="444 741 1474 930"> \$("#div.calendar_menu_body td.fc-day").click(function() { var preferredDefaultTime = "09:00"; var dateFromFieldId = "date_from"; window.location = "calendarViewEditable?" + dateFromFieldId + "=" + \$(this).attr("data-date") + "%20" + preferredDefaultTime; }); </pre>
Event Click Callback (Javascript)	<p>Custom Javascript code to execute when a calendar event is clicked on.</p> <div data-bbox="435 1014 1484 1083" style="background-color: #f0f0f0; padding: 5px;">Sample Code to open up form view in a popup dialog</div> <pre data-bbox="444 1098 1474 1203"> var popupActionDialog = new PopupDialog("EventFormMenuId?id="+event.id+"&embed=true"); popupActionDialog.init(); </pre>



Show in JPopup Dialog

```
var address = "EventFormMenuId?embed=true&id=" + event.id;  
JPopup.show("testPopup", address, {}, "View Item", "50%", "50%");
```



Time Display Format	Refer to https://fullcalendar.io/docs/date-formatting-string for formats. <div style="border: 1px solid #ccc; padding: 5px; margin: 5px 0;"> <p>Example</p> <pre>h(:mm)t //2:12p, 1p HH:mm //14:12, 13:00 hh(:mm)t //02:12p, 01p</pre> </div>
Custom Header (HTML)	Custom header in HTML to show on the top of the calendar.
Custom Footer (HTML)	Custom footer in HTML to show on the bottom of the calendar.

Performance & Offline

Cache Settings

Name	Description
Scope	Caching options are: <ul style="list-style-type: none"> • None: No caching. • Application: Cache content by application where all users will see the same content. • User: Cache by username.
Duration (s)	Duration in seconds to cache content, defaults to 20 seconds if applicable.

Read more at [Performance Improvement with Userview Caching](#).

PWA Offline Settings

Note: PWA Offline support is dependent on the theme used.

Name	Description
Enable cache for offline support	Enable caching for offline support, usually set for use on mobile browsers.

Read [Progressive Web Application \(PWA\)](#) for more information.

Download Demo App

- [Calendar Menu App](#) in Joget Marketplace (Note: For Joget Workflow v5 only)
- [APP_calendarTest-sample.jwa](#) - Sample use of **Event After Rendering Callback** field

