

# MobileUtil

- [Description](#)
- [Code Sample](#)
- [Fields](#)
  - [MOBILE\\_VIEW](#)
- [Methods](#)
  - [isMobileDisabled](#)
  - [isMobileUserAgent](#)
  - [isMobileUserAgent](#)
  - [isMobileView](#)
  - [setDisableMobile](#)
  - [setMobileView](#)

## Description

- org.joget.apps.app.service.MobileUtil
- Under wflow-core module
- Utility classes for mobile related features.

## Code Sample

```
import org.joget.apps.app.service.MobileUtil;

if (MobileUtil.isMobileView()) {
    //return mobile html template
} else {
    //return normal html template
}
```

## Fields

[MOBILE\\_VIEW](#)

```
public static final String MOBILE_VIEW = "_mobileView_";
```

A key used to set the HTTP request attribute when it is a mobile view.

## Methods

[isMobileDisabled](#)

```
public static boolean isMobileDisabled()
```

Flag to indicate the mobile support is disabled by system

[isMobileUserAgent](#)

```
public static boolean isMobileUserAgent()
```

Checks whether the current thread is being called from a mobile browser

[isMobileUserAgent](#)

```
public static boolean isMobileUserAgent(javax.servlet.http.HttpServletRequest request)
```

Checks whether the current request is being called from a mobile browser

[isMobileView](#)

```
public static boolean isMobileView()
```

Checks whether the current request is a mobile view

[setDisableMobile](#)

```
public void setDisableMobile(boolean disabled)
```

Sets to disable the mobile support

```
setMobileView
```

```
public static void setMobileView(javax.servlet.http.HttpServletRequest request, java.lang.Boolean mobileView)
```

Sets a flag to indicate whether or not the current request is a mobile view.