

Pre-populate Form Select List from External Source

To pre-populate a single form select list from an external source, choose the select field and click on 'Edit'.

Parent Information

Drag This Column

First Name *

Last Name *

Email Address *

Relationship Category

Mom

Under the 'Choose Options Binder' menu, click on 'Bean Shell Form Binder' in the Options Binder select field.

Auto :

Edit Select Box ?

Edit Select Box > Or Choose Options Binder (Bean Shell Form Binder) > Advanced Options

ID *

relationshipCat

Label

Relationship Category

Options (Hardcoded)

VALUE	LABEL	GROUPING
<div></div>		

Or Choose Options Binder

Bean Shell Form Binder

Under 'Configure Bean Shell Form Binder', enter your Bean shell script to populate the select fields. For each row that you add to the FormRowSet, be sure to put the 'FormUtil.PROPERTY_VALUE' and 'FormUtil.PROPERTY_LABEL' fields in the FormRow that will be added to the FormRowSet.

+

Auto save when close?

×

Configure Bean Shell Form Binder ?

⌵

Edit Select Box > Configure Bean Shell Form Binder > Advanced Options

Script *

1 import org.joget.apps.form.model.*;
2 import org.joget.apps.form.service.*;
3
4 public FormRowSet test() {
5 FormRowSet f = new FormRowSet();
6 f.setMultiRow(true);
7
8 FormRow r1 = new FormRow();
9 r1.put(FormUtil.PROPERTY_VALUE, "test1");
10 r1.put(FormUtil.PROPERTY_LABEL, "tester1");
11 f.add(r1);
12
13 FormRow r2 = new FormRow();
14 r2.put(FormUtil.PROPERTY_VALUE, "test2");
15 r2.put(FormUtil.PROPERTY_LABEL, "tester2");
16 f.add(r2);
17
18 return f;
19 }
20
21 return test();

This field is mandatory

Use AJAX for Cascade Options? ?

☐

Form Options Caching

⌵

Sync Cache Interval ?

```
import org.joget.apps.form.model.*;
import org.joget.apps.form.service.*;

public FormRowSet test() {
    FormRowSet f = new FormRowSet();
    f.setMultiRow(true);

    FormRow r1 = new FormRow();
    r1.put(FormUtil.PROPERTY_VALUE, "test1");
    r1.put(FormUtil.PROPERTY_LABEL, "tester1");
    f.add(r1);

    FormRow r2 = new FormRow();
    r2.put(FormUtil.PROPERTY_VALUE, "test2");
    r2.put(FormUtil.PROPERTY_LABEL, "tester2");
    f.add(r2);

    return f;
}

return test();
```

Of course, you would want to populate the values for `PROPERTY_LABEL` and `PROPERTY_VALUE` from your external datasource. For more information on how to connect to a database source, see the example code within ['Pre-populate Form Fields with Data from External Source'](#) or [this example on the Joget Blog](#).

Related Elements

- Bean Shell Form Binder
- Select Box

