

API Authenticator Plugin

- [Usages](#)
- [POM file adjustments](#)
- [Abstract Class](#)
 - [org.joget.api.model.ApiAuthenticatorAbstract](#)
 - [Abstract Methods](#)
 - [authenticate](#)
- [Plugin Properties Options](#)
- [Sample Plugins](#)

Usages

- **API Authenticator Plugin** is used as an extension or replacement for the default authentication methods available in the API Builder.
- This plugin type must extend **org.joget.api.model.ApiAuthenticatorAbstract** abstract class.

POM file adjustments

- Add the project dependencies below:

```
<!-- Add this dependency for authenticate(...) params -->
<dependency>
  <groupId>javax.servlet</groupId>
  <artifactId>jsp-api</artifactId>
  <version>2.0</version>
</dependency>

<!-- Add apibuilder_api dependency -->
<dependency>
  <groupId>org.joget.api</groupId>
  <artifactId>apibuilder_api</artifactId>
  <version>${project.version}</version>
  <scope>provided</scope>
</dependency>
```

Abstract Class

org.joget.api.model.ApiAuthenticatorAbstract

- Under **apibuilder_api** module
- Extended **org.joget.plugin.base.ExtDefaultPlugin**. Please refer to [Plugin Base Abstract Class and Interface](#).
- Implemented **org.joget.plugin.property.model.PropertyEditable**. Please refer to [Plugin Base Abstract Class and Interface](#).
- Implemented **org.joget.api.model.ApiAuthenticator**.
- A base abstract class to develop a custom API Authenticator Plugin.

Abstract Methods

[authenticate](#)

```
public boolean authenticate(HttpServletRequest request, HttpServletResponse response);
```

Used to authenticate API calls on an existing API document.

Parameters:

request - the http request information

response - the http response to write

Plugin Properties Options

- Please refer to [Plugin Properties Options](#) for more information.

Sample Plugins

- Basic Authenticator - [basic-authenticator.zip](#)